


**WoodChic Premium Designer Flooring (Specification Data)****FLOORING PROPERTIES & PACKAGING**

<b>Type of Construction:</b>	Commercial Grade Loose Lay Luxury Vinyl Tile
<b>Collection:</b>	WoodChic Designer Series
<b>Use:</b>	Commercial
<b>Size:</b>	7.25" Width X 60" Length (184mm X 1524mm)
<b>Installation Method:</b>	Glue Down
<b>Certification:</b>	FloorScore certified by SCS Global Services
<b>Wear Layer:</b>	20mil (0.5mm)
<b>Edge Detail:</b>	Beveled Edge
<b>Emboss:</b>	Natural Wood Texture
<b>Gauge:</b>	5mm Total Thickness
<b>Planks/Case:</b>	8
<b>Coverage/Each Plank:</b>	3.02 Sq. Ft. (0.28 Sq. Meters)
<b>Coverage/Case:</b>	24.11 Sq. Ft. (2.24 Sq. Meters)
<b>Coverage/Pallet:</b>	50 Cases/Pallet (1205.5 Sq. Ft. / 112 Sq. Meters)
<b>Warranty:</b>	20-Year Limited Commercial


# STANDARDS

Standard	Feature	Performance	
		9 in*60 in*0.5mm	7.25 in*60 in*0.5mm
ASTM F970	Static Load	Passes - 1000 psi	Passes - 1000 psi
ASTM F2199	Dimensional Stability	Passes	Passes
ASTM F1914	Residual Indentation	Passes	Passes
ASTM F1514	Resistance to Heat	Passes - less than 8.0 Delta E.	Passes - less than 8.0 Delta E.
ASTM F1515	Resistance to Light	Passes - less than 8.0 Delta E.	Passes - less than 8.0 Delta E.
ASTM F925	Resistance to Chemicals	Passes - no change	Passes - no change
ASTM E648	Critical Radiant Flux	Passes - >0.45 watts/cm <sup>2</sup> , Class 1	Passes - >0.45 watts/cm <sup>2</sup> , Class 1
ASTM D2047	Coefficient of Friction, Slip Resistance	Meets SCOF for ADA walking surfaces	
ASTM F410	Wear Layer	Passes	Passes
ASTM D4060	Abrasion Resistance	Passes	Passes
ASTM D7027	Hoffman Scratch	Passes	Passes
EN 16094	Micro-Scratch Resistance (A & B)	Passes	Passes


## Recommend Installation Options:



Ashlar



Stagger



Random